


# Datasheet Actuation Module: *Curve*® unplugged 1910E24



- Active length: **19 mm**
- Module size: **39 mm x 10 mm x 3.3 mm**
- Bending: **low (E24)**
- Module weight: **1.9 g**


## Hosting structure and actuation module



- Example hosting structure: stainless steel 0.55 mm
- Load range with high cycling stability ( $> 300.000$ )

at module edge:	690 g
at 25 mm:	370 g
at 50 mm:	250 g

## Actuation module



- Operating mode: **unplugged**
- Thermal activation by: external heating
- Possible external heating: convection, radiation, conduction
- Maximum temperature:
 

130°C	permanent
>150°C	short-term

© CompActive GmbH



All values are only estimations!

## Customized high performance actuation modules by ...




### ... high-tech solutions

- reliable load transfer
- proven cycle stability
- injection molded frame elements
- special SMA material specifications
- high temperature FRP
- self-sensing capability



### ... individual design

- substrate (metals, polymers)
- size
- deflection
- load / cycles
- wire material / temperatures
- electrical resistance



### ... customized mechanical fixation

- adhesive films
- liquid adhesives
- bolts, rivets, screws
- plug-on

### ... various electrical connection

- crimping
- soldering
- plugging in
- welding



© CompActive GmbH